



ENGINEERING DATA SHEET

GDK11 TAS

50Hz

CCN: 47825235001
Rev.: A
ECN: 1491576
Sheet: 2 of 5
Date: 2023.07

Model			GDK11-7A TAS	GDK11-8A TAS	GDK11-10A TAS	GDK11-12.5A TAS
GENERAL PERFORMANCE DATA						
Rated discharge Pressure		barg	7	8	10	12.5
Maximum Operating Pressure	(2)	barg	7.2	8.2	10.2	12.7
Minimum Operating Pressure		barg	4.5	4.5	4.5	4.5
Maximum Operating Ambient Temperature		°C	40	40	40	40
Minimum Operating Ambient Temperature		°C	2	2	2	2
Maximum System Temperature Setting		°C	109	109	109	109
Nominal Power - Main Motor		kW	11	11	11	11
Main Motor Efficiency	(3)	%	91.2%	91.2%	91.2%	91.2%
Capacity FAD	(1)	m³/min	1.69	1.58	1.41	1.23
Package Input Power with Fan - Air Cooled	(4)	kW	13.4	13.4	13.1	13.2
Package Input Power with Fan&Dryer - Air Cooled	(4)	kW	14.1	14.1	13.8	13.9
Specific Power - Air Cooled	(4)(5)	kW/m³/min	7.9	8.5	9.3	10.7
Specific Power with Dryer - Air Cooled	(4)(5)	kW/m³/min	8.3	8.9	9.8	11.3
SOUND LEVEL						
Noise Level Standard Package - Air Cooled	(6)	Sound Pressure - dB(A)	66	66	66	66
Noise Level Standard Package - Air Cooled		Sound Power - dB(A)	81	81	81	81
OIL CARRY OVER						
		mg/m³	≤5	≤5	≤5	≤5
COOLING DATA (@ Maximum Ambient Temperature & Maximum Discharge Pressure)						
Heat Removal (Oil Cooler)		kW	10.8	10.8	10.8	10.8
Heat Removal (Oil and Aftercooler)		kW	12.8	12.8	12.8	12.8
Permitted Additional Static Pressure		Pa	30	30	30	30
Fan Air Flow		m³/min	35.4	35.4	35.4	35.4
Cooling Air Temperature Rise @ 40°C		°C	16	16	16	16
Aftercooler CTD	(7)	°C	10	10	10	10
AIR END DATA						
Main Rotor Speed		RPM	6600	6300	5750	5100
Tip Speed Rotor		m/sec	25.66	24.49	22.35	19.83
Full Load Shaft Power		kW	10.98	11.07	11.2	11.2
COOLANT LUBRICATION DATA						
Total Coolant Capacity - Air Cooled	(12)	litres	4.5	4.5	4.5	4.5
PIPING CONNECTIONS						
Air Discharge	(8)	Inches Rc	0.75 INCH (FEMALE)	0.75 INCH (FEMALE)	0.75 INCH (FEMALE)	0.75 INCH (FEMALE)
Coolant Drain - Hose Size		Inches UNF	0.562(FEMALE)	0.562(FEMALE)	0.562(FEMALE)	0.562(FEMALE)
Diameter of Power Inlet		mm (Inches)	25 (1)	25 (1)	25 (1)	25 (1)
DIMENSIONS AND WEIGHT						
Length, Width, Height		mm	1576, 844, 1644	1576, 844, 1644	1576, 844, 1644	1576, 844, 1644
Net Weight - Air Cooled		kg	460	460	460	460
GA Drawing Number - Air Cooled			47825235001	47825235001	47825235001	47825235001
ELECTRICAL DATA						
Motor Speed	(13)	rpm	2935	2935	2935	2935
Motor Protection			TEFC IP55	TEFC IP55	TEFC IP55	TEFC IP55
Starting Method			Y-Δ	Y-Δ	Y-Δ	Y-Δ
Insulation Grade			F	F	F	F
Full Load Package Current - Air Cooled	(9)	Amps @ 380V	21	21	21	21
Main Motor Locked Rotor Current	(14)	Amps @ 380V	203	203	203	203
Package Power Factor			0.89	0.89	0.89	0.89
Electrical Installation						
Recommended Supply Cable Size	(10)	mm²Cu (Kcmil) @ 380V	10	10	10	10
Maximum Recommended Fuse Rating	(10)(11)	Amps @ 380V	50	50	50	50
Refrigerated Dryer Data						
Refrigerant Type-Domestic			R134a	R134a	R134a	R134a
Refrigerant Type-Export			R404a	R404a	R404a	R404a
Refrigerant Quantity		kg	0.25	0.25	0.25	0.25
Fan Air Flow		m³/min	33	33	33	33
Filter Data						
ISO Class Data	(14)	ISO Class (Particles Humidity and Liquid Water, Oil)	[01-0.5µm] ≤20000	Particles 0.5- 1µm ≤400	Humidity and Liquid Water [1- 5µm] ≤10	Total Oil ≤+10°C ≤0. 01

Notes:

- FAD (Free Air Delivery) is full package performance including all losses. Tested per ISO 1217 : 2009 Annex C.
- Maximum pressure at package discharge, value at which compressor will stop when unit operating at maximum target pressure
- IE3 efficiency motor
- Measured at rated capacity and rated pressure
- Specific power guaranteed in accordance with ISO 1217 : 2009 Annex C
- Measured in free field conditions per ISO 2151 using Hemispherical Method; ducted inlet and outlet, with + 3 dB(A) tolerance
- CTD based on 100°F/38°C inlet air at 40% Relative Humidity (For alternate conditions contact Ingersoll Rand)
- "Rc" Thread for domestic standard
- Maximum current includes 5% additional current due to fouled filters and elements
- 90°C copper cables, Always apply local electrical codes for sizing cables and system protection
- Time delay fuse recommended. Apply local electrical codes for fuse sizing
- Coolant volumes listed are approximate. See operator manual for coolant fill procedure
- 50Hz (±2%) motor voltage tolerance: (380V)±7% ;
- Star-Delta starting current inrush is about 33% of direct starting current
- During the Star-Delta open-starting transition, the in-rush current value could instantaneously peak from 1.8 to 2.8 times the noted Locked-Rotor-Amperage (LRA) values
- TAS units deliver ISO Class 1-4.2 quality air measured at steady state conditions in accordance with ISO 8573-1:2010, with inlet air to package of 25 °C (77°F) and RH of 60%
- Package discharge pressure=rated pressure-0.5bar(include water moisture, H-efficiency filter, dryer and tube pressure drop)

Product Improvement is a continuing goal at Gardner Denver. Design and specifications are subject to change without notice or obligation.